



IPS[®]

WELD-ON

WELD-ON 57

PLASTIC CLEANER

SUBSTRATE RECOMMENDATIONS

WELD-ON 57 is a cleaner for a wide variety of plastics, such as acrylics, polycarbonate, butyrate, Vinyl, ABS, Styrene, etc.

APPLICATION RECOMMENDATIONS

WELD-ON 57 can be used on many kinds of plastic furniture or fixtures, signs, T.V. screens, aircraft and boat windshields, display items, stereo dust covers, vinyl upholstery, etc. It is widely used by plastic shops as a multi-use cleaner.

GENERAL DESCRIPTION

An all purpose plastic cleaner. Helps decrease the static charge and to reduce the accumulation of dust. Unlike harsh cleaners, it does the job without abrasives. It removes masking tape adhesive, and with one application, cleans fast, leaving a high quality, bright finish, free of residue or oily film. However, some surfaces may be adversely affected upon application. THE SUITABILITY OF THE CLEANER FOR EACH APPLICATION SHOULD BE VERIFIED ON SCRAP MATERIAL BEFORE ACTUAL USE.

DIRECTIONS FOR USE

- Apply with a clean, lint free cloth, sponge or chamois.
- If very dirty, avoid rubbing, as you may scratch the surface.
- If drying is necessary, use a clean, damp cloth to remove excess moisture.

SHELF LIFE

Three years expectancy in tightly sealed containers.

SHIPPING

Shipping Information for Individual Containers Larger than One Liter: DOT Shipping Name: Alcohol, n.o.s. (Denatured Alcohol). DOT Hazard Class: 3. ID #: UN1987. Packaging Group: II. Label: Flammable Liquid.

Shipping Information for Less than One Liter: DOT Shipping Name: Consumer Commodity. DOT Shipping Class: ORM-D. SAFETY AND ENVIRONMENTAL PRECAUTIONS

Weld-On 57 is a flammable, fast evaporating, plastic cleaner. It is considered a hazardous material. In conformance with the Federal Hazardous Substances Labeling Act, the following hazards and precautions are given. Purchasers who may re-package this product must also conform to all local, state and federal labeling, safety and other regulations.

CAUTION! – FLAMMABLE – VAPOR HARMFUL

MAY BE HARMFUL IF SWALLOWED – POISON – MAY IRRITATE SKIN OR EYES

Keep out of reach of children. Do not take internally. Keep away from heat, spark, open flame and other sources of ignition. Keep container closed when not in use. Store in the shade between 40°F and 80°F. Use only with adequate ventilation. Avoid breathing of vapors. Atmospheric levels should be maintained below established exposure limit values contained in Section II and VIII of the Material Safety Data Sheet. If airborne concentrations exceed those limits, use of a NIOSH-approved organic vapor cartridge respirator with full face-piece is recommended. The effectiveness of an air-purifying respirator is limited. Use it only for a single short-term exposure. For emergency and other conditions where short-term exposure guidelines may be exceeded, use an approved positive pressure self-contained breathing apparatus. Do not smoke, eat or drink while working with this product. Avoid contact with skin, eyes and clothing. May cause eye injury. Protective equipment such as gloves, safety goggles and impervious apron should be used. Carefully read Material Safety Data Sheets and follow all precautions. Contains Denatured Alcohol (64-17-5). Do not use this product for other than intended use.

"Title III Section 313 Supplier Notification": This product contains toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of 40CFR372. This information must be included in all MSDS's that are copied and distributed for this material.

FIRST AID

Inhalation: If ill effects from inhalation, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call physician.

Eye or Skin Contact: Flush with plenty of water for 15 minutes. If irritation persists, get medical attention.

Ingestion: If swallowed, do not induce vomiting. Contact physician immediately.

QUALITY ASSURANCE

Every batch of this cement is checked to assure that consistent quality is maintained. An infrared absorption curve is recorded for each batch to ensure that this cement is properly formulated. Samples are taken from all batches and kept for a period of at least one year. A batch identification code is stamped on each can.

IMPORTANT NOTE

This product is intended for use by skilled individuals at their own risk. These suggestions and data are based on information we believe to be reliable. Users should verify by test that this product, as well as these methods, are suited to their application. Since specific use, materials and handling are not controlled by IPS, our warranty is limited to the replacement of defective IPS products.