

Soft-Guard PLUS™



Soft ADA-Compliant Under Lav Piping Covers

Cut-To-Fit Design Eliminates
Additional Extension
Parts & Tape!

Protect
Wheelchair
Users from
Possible Burns
& Abrasions

PVC Insulated
Material Maximizes
Protection While
Meeting ADA &
UPC Standards

25 Flame/450
Smoke
Index*



Fast-Install Hook & Loop
Fastening

- Durable Fusion-Welded Seams
- 1/8" Pliable PVC Shell Finish Compliments Fixtures
- Anti-Microbial, UV-Inhibited, Anti-Fungal
- Fits Schedule 40 Traps & Flexible Braided Supplies

* Base material tested in accordance with Testing Standard ASTM E 84-07 with a 25 flame spread/450 smoke index (not for Plenum use).

Soft-Guard PLUS™



Code Compliance Minimizes Risk

Complies with Americans with Disabilities Act (ADA) Laws & UPC Standards

ADA 4.19.4, ICC/ANSI A117.1 (sec. 606.6). Protects wheelchair users from cuts, burns and abrasions.

Soft-Guard PLUS Fits the Following P-Trap Sizes:

1-1/4" Tubular/Cast Brass

1-1/2" Tubular/Cast Brass

1-1/2" Tubular Plastic with Wing Nuts

1-1/2" Schedule 40 Plastic with Swivel Nuts

Available Soft-Guard PLUS Products:

Item #	Description	Case Qty	UPC
82521	25/450 Soft-Guard Plus Water Valve cover	10	012181825211
82522	25/450 Soft-Guard Plus P-Trap cover	10	012181825228
82523	25/450 Soft-Guard Plus Offset cover	10	012181825235
82524	25/450 Soft-Guard Plus P-Trap & 1 valve covers	10	012181825242
82525	25/450 Soft-Guard Plus P-Trap & 2 valve covers	10	012181825259

PVC Base Insulation Material Complies with 25 Flame Spread/450 Smoke Index*

Accessibility Requirements: ADA 4.19.4, (ADA/ABA 606.5 rev.) and ICC/ANSI A117.1, (sec.606.6).

Specification: Insulate all drainage piping including hot and cold water valve and supplies under lavatories to meet ADA (Americans with Disabilities Act) and UPC (International Building Code).

*Base material tested in accordance with Testing Standard ASTM E 84-07 with a 25 flame spread/450 smoke index (not for Plenum use).

Soft-Guard PLUS Installation Instructions:

1. Measure and trim Soft-Guard PLUS with scissors to size needed
2. Place Soft-Guard PLUS cover over P-Trap or Valve & Supply
3. Secure in position by joining internal Hook & Loop fastening system
4. For improved tamper resistance and tighter custom fit, insert snap-to-lock fasteners through pre-drilled holes and press together to lock

IPS
CORPORATION

500 Distribution Parkway
Collierville, TN 38017
Customer Service: 800-888-8312
Fax: 901-853-5008
website: www.ipscorp.com

